



Product Guide

	Model name	Thickness (mm) (inch)	Compressibility	Heat set		Cold set	Sheetfed							Image reproductively Solid	Image reproductively Dot	Paper release	Sticky back	Comment
				Coated paper	Rough paper		Thick	Thin	Varnish	UV	Perfactor	small offset	Metal					
Sheetfed	FIT 10	1.68 / 1.95 0.067 / 0.077	Semi soft	—	—	—	○	○	—	—	○	○	○	○	◎	◎	—	High quality sheetfed. High-end printing.
	FS-50	1.68 / 1.95 0.067 / 0.077	Semi hard	—	—	—	○	○	—	—	○	○	◎	◎	○	○	—	General sheetfed. Higher color, good smash recovery.
	FS-70	1.68 / 1.95 0.067 / 0.077	Semi hard	—	—	—	○	—	—	○	—	—	○	○	—	○	—	Sheetfed. Hybrid & superior anti-dust pilling.
	FS-100	1.68 / 1.95 0.067 / 0.077	Semi hard	—	—	—	○	—	—	◎	—	—	○	○	○	○	—	Sheetfed. Metal decoration. UV only.
	FIT UV	1.68 / 1.95 0.067 / 0.077	Semi soft	—	—	—	○	—	—	◎	—	—	○	○	○	○	—	Sheetfed, Metal decoration. UV only.
Heatset Web	FIT Web	1.68 / 1.95 0.067 / 0.077	Semi soft	◎	◎	—	—	—	—	—	—	—	—	○	◎	○	—	Heatset on Rougher Paper.
Coldset Web (News paper)	FIT News	1.68 / 1.95 / 2.10 0.067 / 0.077 / 0.082	Semi soft	—	—	◎	—	—	—	—	—	—	—	○	◎	○	—	General newspaper printing. Negative paper feeding.
Business Form	FIT Form	0.95 / 1.05 0.037 / 0.041	Semi soft	—	—	—	—	—	—	—	—	—	—	○	◎	—	○	Business form, Envelope printing. Hybrid, Sticky back type.
Varnish	FP-75	1.68 / 1.95 0.067 / 0.077	Soft	—	—	—	—	—	◎	—	—	—	—	—	—	—	○	Stripping blanket for coating.
Under	FUJI PAT	0.5 / 0.8 / 1.0 0.025 / 0.040	Soft	—	—	—	—	—	—	—	—	—	—	—	—	—	—	Under packing blanket.

Contact


FUJIKURA RUBBER LTD. 2-11-20 Nishi-Gotanda Shinagawa Tokyo Japan 141-0031
藤倉ゴム工業株式会社 TEL : +81(3)-3490-2126 FAX : +81(3)-3490-2150 E mail : info@fujikuragraphics.com

FUJIKURA GRAPHICS obtained ISO 14001 Certification for environmental management system, and ISO 9001 Quality System Certification.

The content described in this catalog is the one as of June, 2009. The specification and the appearance of each product might change without a previous notice for the improvement.

